

## **Gunnsy** 2313-3-5



|                          |                | A** - A | 150°                  | 180°   | 150°          |           |
|--------------------------|----------------|---------|-----------------------|--|---------------|-----------|
| Lightsource Type:        | LED (built in) |         |                       |  | $\checkmark$  |           |
| System Power [W]:        | 8W             |         |                       |  |               |           |
| CCT (Color Temperature): | 3000K          | 120°    | k / X                 | $\sim$ 7                                     |               | 120°      |
| CRI / Ra:                | 80             |         |                       | $\prec$   $\prec$                            | $\setminus X$ |           |
| Lumen Output:            | 458lm          |         |                       |  |               |           |
| Lumen LED (tc=25):       | 500lm          |         |                       | $\langle \rangle \downarrow \rangle \rangle$ |               |           |
| Beam Angle:              | 35°            |         |                       |  |               |           |
| Lens (Diffuser):         | Clear          | 90°     |                       |  |               | 90°       |
| Dimming:                 | Phase-Cut      |         | $       \rangle$      | 400  | . / / /       |           |
| System Voltage [V]:      | 230V 50Hz      |         |                       |  | $\times$ / /  |           |
| Connection:              | Cable 2m       |         |                       | 800  |               |           |
| Mounting:                | Ground         |         | $ \land \land \land$  | 1200   |               |           |
| Lumen/W:                 | 57lm/W         | 60°     | $  \setminus \rangle$ |  |               | 60°       |
| Height [mm]:             | 85mm           |         |                       | 1600   | $\times$      |           |
| Width [mm]:              | 55mm           |         |                       | 2000   |               |           |
|                          |                |         | 30°<br>- C0 / C180    | 0°   | 30° C 90      | <br>/C270 |

All specifications are nominal values, deviations may occur.

Product specifications are subject to change without notice. Electrical equipment designed to be part of a fixed electrical installation can only be installed by a registered installation company cd / 1000 lm