

Delock LTE Antenna SMA -0.8 ~ 3.0 dBi Omnidirectional With Flexible Joint Black

Description

This LTE antenna can be connected to your LTE device with SMA connector in order to receive or to send a signal.



Specification

- LTE Band 1/2/3/7/8/13/17/20
- 1920 ~ 2170 MHz(1), peak gain 1,7 ~ 2,3 dBi
- 1710 ~ 1880 MHz (3), peak gain 1,8 ~ 3,0 dBi
- 2500 ~ 2690 MHz (7), peak gain 2,0 ~ 2,7 dBi
- 880 ~ 960 MHz (8), peak gain 0,6 ~ 0,5 dBi
- 746 ~ 787 MHz (13), peak gain 0,3 ~ 0,9 dBi
- 704 ~ 746 MHz (17), peak gain 0,3 ~ 0,7 dBi
- 791 ~ 862 MHz (20), peak gain - 0,8 ~ 0,2 dBi
- GSM
- UMTS
- WLAN 2,40 GHz
- Bluetooth
- SMAplug screw interface
- With flexible joint
- Polarization: linear, vertical
- Impedance: 50 Ohm
- Operating temperature: -10 °C ~ 55 °C
- ABS UV resistant
- Dimension: with flexible joint 135.00 mm
without flexible joint 107.00 mm
- Ø: 19.00 mm (top)
10.20 mm (base SMA)

Item No. 88571

EAN	4043619885718
Country of origin	Taiwan, Republic of China

Package content

- Antenna

Package

- Poly bag