



## Reduktion PE100 SDR17/17,6

- Spidsende, stuk/el svejsning

d [mm]	d1 [mm]	code	SP	weight [kg]
90	63	<b>753 900 872</b>	40	0,224
90	75	<b>753 900 870</b>	40	0,234
110	63	<b>753 900 877</b>	30	0,326
110	90	<b>753 900 876</b>	16	0,333
125	63	<b>753 900 882</b>	10	0,610
125	90	<b>753 900 881</b>	1	0,461
125	110	<b>753 900 880</b>	1	0,507
140	75	<b>753 900 886</b>	14	0,560
140	90	<b>753 900 887</b>	14	0,642
140	110	<b>753 900 884</b>	12	0,715
140	125	<b>753 900 885</b>	12	0,754
160	90	<b>753 900 888</b>	10	0,752
160	110	<b>753 900 890</b>	10	0,930
160	125	<b>753 900 889</b>	10	0,930
160	140	<b>753 900 831</b>	10	0,995
180	90	<b>753 900 873</b>	8	1,010
180	110	<b>753 900 874</b>	8	1,600
180	125	<b>753 900 891</b>	8	1,165
180	140	<b>753 900 875</b>	8	1,720
180	160	<b>753 900 832</b>	8	2,100
200	140	<b>753 900 866</b>	1	1,800
200	160	<b>753 900 892</b>	6	1,664
200	180	<b>753 900 893</b>	5	2,580
225	140	<b>753 900 867</b>	4	2,021
225	160	<b>753 900 896</b>	4	2,020
225	180	<b>753 900 895</b>	4	2,240
225	200	<b>753 900 894</b>	8	2,237
250	160	<b>753 900 800</b>	7	2,850
250	180	<b>753 900 868</b>	6	3,100
250	200	<b>753 900 801</b>	6	3,210
250	225	<b>753 900 802</b>	6	2,385
280	200	<b>753 900 898</b>	6	3,800
280	225	<b>753 900 899</b>	5	4,100
280	250	<b>753 900 803</b>	5	4,352
315	200	<b>753 900 804</b>	2	5,390
315	225	<b>753 900 807</b>	4	6,200
315	250	<b>753 900 805</b>	4	6,420
315	280	<b>753 900 806</b>	4	5,940
355	250	<b>753 900 808</b>	1	7,082
355	280	<b>753 900 809</b>	2	6,728
355	315	<b>753 900 810</b>	2	7,240
400	280	<b>753 900 811</b>	2	7,930
400	315	<b>753 900 812</b>	2	9,949
400	355	<b>753 900 813</b>	2	9,620
450	280	<b>753 900 814</b>	2	11,500
450	315	<b>753 900 815</b>	2	11,805
450	355	<b>753 900 816</b>	2	11,900
450	400	<b>753 900 817</b>	2	12,964
500	315	<b>753 900 818</b>	2	15,500
500	355	<b>753 900 819</b>	2	15,700
500	400	<b>753 900 820</b>	1	16,200
500	450	<b>753 900 821</b>	2	17,000
560	355	<b>753 900 822</b>	1	21,400
560	400	<b>753 900 823</b>	1	21,700
560	450	<b>753 900 824</b>	1	22,300
560	500	<b>753 900 825</b>	1	23,200
630	400	<b>753 900 826</b>	1	29,700
630	450	<b>753 900 827</b>	1	30,100
630	500	<b>753 900 828</b>	1	30,800
630	560	<b>753 900 829</b>	1	31,900

# Datasheet

gültig ab: 11-06-14



d [mm]	d1 [mm]	code	SP	weight [kg]
710	500	<b>753 900 833</b>	1	58,796
710	560	<b>753 900 834</b>	1	60,578
710	630	<b>753 900 835</b>	1	62,448
800	560	<b>753 900 836</b>	1	75,842
800	630	<b>753 900 837</b>	1	78,255
800	710	<b>753 900 838</b>	1	80,504
900	630	<b>753 900 839</b>	1	99,282
900	710	<b>753 900 840</b>	1	100,908
900	800	<b>753 900 841</b>	1	103,578
1000	710	<b>753 900 842</b>	1	124,232
1000	800	<b>753 900 843</b>	1	125,277
1000	900	<b>753 900 844</b>	1	126,638

The technical data are not binding and not expressly warranted characteristics of the goods. They are subject to change. Our General Conditions of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.piping.georgfischer.com>