

NEOFLEX® EPDM are highly flexible EPDM rubber hoses with braiding (see technical specification). Excellent functional and mechanical properties. For use in technical water supply systems.



Technical specifications :

Article no.	S400	S404	S410	S425	S500	S503	S504	S507
Nominal size	DN10				DN13			
Inside diameter hose	Ø9,5				Ø12			
Outside diameter hose, without braiding	Ø13,5				Ø17,0			
Stainless steel braiding	x	-	-	-	x	-	-	-
Galvanized braiding	-	-	-	-	-	x	-	-
Polyamid braiding	-	blue	black	white	-	-	blue	black
Colour stripe	-	-	-	red+blue	-	-	-	-
Max. work pressure	10 bar							
Max. temperature	90 °C							
Min. flow at 3 bar	45 l/min				60 l/min			
Approvals	-							

Standard fittings :

	Female elbow		Female			Tube			Male long		Male short		Male			Comp. joint					
	3/8"	1/2"	3/4"	3/8"	1/2"	3/4"	Ø8	Ø10	Ø15	M8x1	M10x1	M8x1	M10x1	3/8"	1/2"	3/4"	Ø8	Ø10	Ø12	Ø15	
DN6				x	x		x	x		x		x	x								
DN8	x	x	x	x	x	x		x			x	x	x	x	x		x	x	x		
DN10	x	x	x	x	x	x									x	x					
DN13		x	x		x	x			x						x	x					x

(Other fittings on request)

Applications* :



Dish washer



Washing machine



Toilet

*For other purposes, please contact Neoperl Nordic A/S

Illustrations are only intended as a guide
 Technical data can be changed without notice

NeoFlex® EPDM are highly flexible EPDM rubber hoses with braiding (See technical specification). Excellent functional and mechanical properties. For use in technical water supply systems.



Technical specifications :

Article no.	S600	S700	S703	S704	S705	S800	S801	S803
Nominal size	DN15	DN20			DN25			
Inside diameter hose	Ø16	Ø19			Ø25			
Outside diameter hose, without braiding	Ø22	Ø26			Ø34			
Stainless steel braiding	x	x	-	-	-	-	x	-
Galvanized braiding	-	-	-	-	x	-	-	x
Polyamid braiding	-	-	blue	black	-	blue	-	-
Colour stripe	-	-	-	-	red	-	-	red
Max. work pressure	10 bar							
Max. temperature	90°C							
Min. flow at 3 bar	96 l/min	145 l/min			-			
Approvals	-							

Standard fittings :

	Female elbow		Female			Tube			Male		Comp. joint
	3/4"	1"	1/2"	3/4"	1"	Ø15	Ø22	Ø28	3/4"	1"	Ø15
DN15	x		x	x		x			x		x
DN20	x			x			x		x		
DN25		x			x			x		x	

(Other fittings on request)

Applications* :



Dish washer



Washing machine



Toilet

*For other purposes, please contact Neoperl Nordic A/S

Illustrations are only intended as a guide
 Technical data can be changed without notice