



Slot bracket USB 3.0 pin header 19 pin 1 x internal > 2 x USB 3.0-A female external low profile

Description

This low profile slotblech by Delock is most suitable for installation into a PC slot of a mini PC and expands your system by two external USB 3.0-A ports. Thus you can connect different USB 3.0 devices, like e.g. external enclosure, Card reader, memory etc. Since the USB 3.0-A interface is compatible to its forerunners USB 2.0 and USB 1.1, you can still use your existing USB devices.

Images



Ref.	82976
EAN	4043619829767
Country of origin	China
Customs tariff number	84718000

Specification

- Connector: internal 4 x USB 3.0-A male
external 4 x USB 3.0-A female
- Cable gauge: 28 AWG
- Current output: max. 900 mA per each USB port
- Voltage: 5 V
- Data transfer rate up to: Super-Speed 5 Gb/s,
High-Speed 480 Mb/s,
Full-Speed 12 Mb/s,
Low-Speed 1.5 Mb/s
- Downwards compatible to USB 2.0 and USB 1.1
- Cable length: ca. 40 cm (without connector)

System requirement

- PC with a free slot
- PC with four free USB 3.0 Ports

Note: For operation of four devices at the same time, which require more than 900 mA for each device, you may need to connect an additional power supply for the connected device.

Package content

- Slot bracket

Package

- Delock poly bag