

Item No. 87298

Delock USB Type-C™ 3.1 Docking Station 4K

Description

This docking station by Delock can be connected to a computer with a USB-C™ Alt-Mode or Thunderbolt™ 3 port and provides a variety of interfaces. Two monitors can be operated simultaneously at the mini Displayport and HDMI outputs, alternatively a single monitor at the VGA output. Three built-in USB Type-A ports allow the use of peripherals, and connections for a headset and gigabit network, as well as an SD / micro SD card reader, complete the features. With a USB-C™ power supply, laptops such as the Macbook or Chromebook can be charged during operation.



Specification

- Connectors:
 - front side:
 - 1 x Gigabit LAN 10/100/1000 Mb/s RJ45 female
 - 1 x mini Displayport 20 pin female
 - 1 x HDMI-A 19 pin female
 - 1 x VGA 15 pin female
 - 1 x USB Type-C™ female (power supply)
 - back side:
 - 3 x USB 3.0 Type-A female
 - 1 x Headset 3.5 mm 4 pin jack
 - 1 x SD / SDHC / SDXC / MMC slot
 - 1 x Micro SD / SDHC / SDXC slot
 - 1 x USB Type-C™ male
- HDMI and Displayport ports support: extended and mirror, resolution up to 2560 x 1440 @ 60 Hz or 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- VGA resolution up to 1920 x 1080 @ 60 Hz
- Transfer of audio and video signals
- Output power: max. 10 W total,
 - 1 x USB Type-A female max. 7.5 W,
 - 2 x USB Type-A female max. 5 W (combined)
- Input power: 1 x USB Type-C™ female max. 60 W
- Metal housing
- Cable length incl. connector: ca. 18 cm
- Colour: silver-grey
- Dimensions (LxWxH): ca. 13.7 x 7.5 x 1.7 cm

System requirements

- Windows 8.1/8.1-64/10/10-64, Windows 10 Mobile, Android ex 6.0, Mac OS ex 10.9
- Device with a free USB Type-C™ port and Displayport alternate mode or with a free Thunderbolt™ 3 port

Package content

- USB-C™ docking station
- User manual

Additional Information

EAN: 4043619872985

Country of origin: China

Package: Retail Box



Images



General	
Specification:	SuperSpeed USB (USB 3.1 Gen 1) Displayport 1.2 High Speed HDMI with Ethernet HDCP 1.4
Supported operating system:	Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Mac ex OS 10.9 Android ex 6.0
Interface	
Output:	1 x RJ45 jack 1 x mini Displayport 20 Pin female 1 x 3.5 mm 4 pin stereo jack female 3 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female 1 x HDMI-A 19 pin female 1 x VGA 15 pin female 1 x SD slot 1 x Micro SD slot
Input:	1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ male 1 x USB Type-C™ female (power supply)
Technical characteristics	
Maximum screen resolution:	3840 x 2160 @ 30 Hz
Signal transmission:	video audio
Voltage:	USB bus powered 1 x USB Type-C™ Power Delivery female (optional for power supply)
Physical characteristics	
Cable length incl. connector:	18 cm
Colour:	silver