



GH-ERGO

Rubber Hammer GH-ERGO

Now with extra long handle for ergonomic working.

The GH-ERGO is equipped with two different rubber elements. One side is equipped with a rectangular, slightly bevelled profile. This way the rubber profile hits the stone flat without the user having to stand too close to the edge of the stone layer. On the second side, the profile is tapered, this enables an accurate strike, e.g. into the grooves of H-stones.

- The extension of the hammer handle from the previous 800 mm to 1000 mm enables an ergonomically upright posture and thus fatigue-free working.
- By using special butyl rubber elements, wrists and elbows are now also protected. The unpleasant springing back when striking is completely eliminated by the damping without reducing the striking power.
- A further helpful feature is the plastic protective disk. This allows height corrections of individual paving stones or slabs that are too high to be made by tapping them on the face without damaging the stone surfaces.

Type	Dead Weight kg (lbs)	Length mm (in)	Order-Number
GH-ERGO	2.9 (6)	1,000 (39¼)	51800113
GH-ERGO-K	2.5 (6)	400 (15¾)	51800114

Spare Part

Type	Description	Order-Number
Rubber cover	for GH-ERGO (2 x bevelled), per piece	36330327
Rubber cover	for GH-ERGO (1 x bevelled), per piece	36330328
Plastic disc	Protective disk for stone (for GH-ERGO)	33250280
Rubber cover	for version GH/GH-K (Order-No. 51800012/51800051), per piece	41800006



top: PB-I, bottom: PB-15/24, right: PB-15/24-L

PAVERBOY PB

For the efficient laying of paving blocks directly from the stack.
Particularly suitable for large blocks.

- Durable surface protection by galvanizing.

PB-I: Two double-T-stones can be picked up and then laid at the same time.

PB-15/24: Hexagonal slabs and similar blocks which cannot be lifted with one hand, can be laid.

PB-15/24-L: With long handles for effortless installation of various types of stones, such as double-T-bricks or large-size paving stones.

Core benefit: At mechanical installation often times single paving stones have to be laid into the gaps to complete the stone bonds. This succeeds easily with the PB-15/24-L in upright body position without bending down.

Type	Dead Weight kg (lbs)	Gripping Range mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
PB-I	1.22 (3)	100 – 170 (4 – 6¾)	10 (20)	51800001
PB-15/24	1.42 (3)	150 – 240 (6 – 9½)	10 (20)	51800004
PB-15/24-L	2.3 (5)	150 – 240 (6 – 9½)	10 (20)	51800115