

# PRODUCT DATASHEET

## CABINET LED Panel 300x100 two light

Cabinet LED Panel | Low voltage undercabinet luminaires with rectangular shape

---

### AREAS OF APPLICATION

- Shelf and undercabinet lighting



---

### PRODUCT BENEFITS

- Low voltage luminaire for DC operation with external driver
- Very slim design
- Homogenous light distribution
- Easy and fast mounting on nearly every surface (adhesive tape or screws)

---

### PRODUCT FEATURES

- Luminous flux: up to 450 lm
- Switch on and off by movements with 5 cm distance in front of the infrared motion sensor
- Stepless dimming by covering the infrared motion sensor in 5 cm distance for at least one second
- Material: aluminum
- Product color: white
- Available as single and double luminaire kit



## TECHNICAL DATA

### Electrical data

<b>Nominal wattage</b>	10.00 W
<b>Operating mode</b>	External LED driver
<b>Nominal voltage</b>	220...240 V
<b>Mains frequency</b>	50/60 Hz

### Photometrical data

<b>Color temperature</b>	3000 K
<b>Color rendering index Ra</b>	≥80
<b>Light color (designation)</b>	Warm White
<b>Luminous flux</b>	550 lm
<b>Luminous efficacy</b>	55 lm/W

### Light technical data


<b>Beam angle</b>	110 ° <sup>1)</sup>
-------------------	---------------------

<sup>1)</sup> ZMP\_110132

### Luminaire sensor data

<b>Type of sensor</b>	Motion
<b>Sensor technology</b>	Infrared/Photocell
<b>Detection range of motion sensor</b>	5 cm

### Dimensions & weight



<b>Length</b>	300.0 mm
<b>Width</b>	100.0 mm
<b>Height</b>	8.0 mm
<b>Product weight</b>	590.00 g
<b>Cable length</b>	1500 mm

## Colors &amp; materials

Body material	Acrylonitrile butadiene styrene (ABS)
Product color	White
Housing color	White

## Temperatures &amp; operating conditions

Ambient temperature range	-20...+40 °C
Temperature range in operation	-20...+40 °C

## Lifespan

Number of switching cycles	100000
Lifespan	30000 h
Rated lamp life time	30000 h

## Additional product data

Mounting type	Surface
Mounting location	Cabinet undersides
Mercury content	0.0 mg

## Capabilities

Dimmable	Yes
Type of connection	Plug type C (EU)
LED module replaceable	Not replaceable

## Certificates &amp; standards

Protection class	II
Type of protection	IP20
Standards	CE/RoHS/EAC
ErP For end-consumer	yes
EEL of included LED module	A++/A+/A

## Logistical data

ErP For end-consumer	yes
----------------------	-----

## EQUIPMENT / ACCESSORIES

- External mains adapter (cable length: 1.5 m) included

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075268302	Folding carton box 1	38 mm x 104 mm x 400 mm	655.00 g	1.58 dm <sup>3</sup>
4058075268319	Shipping carton box 8	392 mm x 226 mm x 171 mm	5523.00 g	15.15 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.