


Geberit PE bøjning



Eksempelbillede



Anvendelser

- Til afløb fra bygninger
- Til afvanding af grunde

Egenskaber

- Kan svejses på begge sider med elektrosvøjsemuffe

- UV-beständig

Tekniske data

Materiale

PE-HD

Varenr.	VVS nr.	DN	d, ø	arc	X	K
360.045.16.1	184036240	40	40 mm	45 °	4 cm	2 cm
361.045.16.1	184036250	50	50 mm	45 °	4.5 cm	2 cm
361.088.16.1	184034250	50	50 mm	88.5 °	6 cm	2 cm
363.045.16.1	184036256	56	56 mm	45 °	4.5 cm	2 cm
363.088.16.1	184034256	56	56 mm	88.5 °	6.5 cm	2 cm
364.045.16.1	184036263	60	63 mm	45 °	5 cm	2 cm
364.088.16.1	184034263	60	63 mm	88.5 °	7 cm	2 cm
365.045.16.1	184036275	70	75 mm	45 °	5 cm	2 cm
365.088.16.1	184034275	70	75 mm	88.5 °	7.5 cm	2 cm
366.045.16.1	184036290	90	90 mm	45 °	5.5 cm	2 cm
366.088.16.1	184034290	90	90 mm	88.5 °	8 cm	2 cm
367.045.16.1	184036310	100	110 mm	45 °	6 cm	2.5 cm
367.088.16.1	184034310	100	110 mm	88.5 °	9.5 cm	2.5 cm
368.045.16.1	184036320	125	125 mm	45 °	6.5 cm	2.5 cm
368.088.16.1	184034320	125	125 mm	88.5 °	10 cm	2.5 cm
369.045.16.1	184036330	150	160 mm	45 °	6.9 cm	2 cm
369.088.16.1	184034330	150	160 mm	88.5 °	12 cm	2.5 cm
370.045.16.1	184036350	200	200 mm	45 °	18 cm	2.5 cm