


MOLDED TYPE

(P2) HD15 MALE INSULATOR: BLACK



CONFIGURATION: (P1)DVI (24+5) F	(P2)HD15 M
C1 ———	<del></del> 1
cs ———	2
<u> </u>	<u> </u>
r.4 ———	_
C5	
0	4 4
8 <del></del>	
/	<u>.</u> _
6 —	<u> </u>
14, 16 ———	<del></del> 9
15 ———	—— 10 <i>,</i> 5
SHIELD —	SHIELD

## NOTES:

- 1. TESTING: 100% OPEN AND SHORT TEST.
- 2. ALL MATERIAL BE ROHS COMPLIANT.

4	CONNECTOR	1PCS	HD15 Male, GOLD PLATED
3	HOOD	1PCS	BLACK PVC MOLDED
2	THUMB SCREW	2PCS	#4-40 UNC TYPE
1	CONNECTOR	1PCS	DVI(24+5) Female, GOLD PLATED
NO.	PARTS NAME	Q'TY	SPECIFICATION

APPROVED	CHECKED	DRAWN	CUSTOMER:	
			ITEM NO.	DVI-6
			DRAW NO.	
			UNIT	mm
			SCALE	NONE

DESCRIPTION:

DVI(24+5) Female/HD15 Male

