


Geberit PE segmentbøjning



Eksempelbillede



Anvendelser

- Til afløb fra bygninger
- Til afvanding af grunde

Egenskaber

- Kan svejses på begge sider med elektrovejsemuffe

- UV-beständig

Tekniske data

Materiale

PE-HD

Varenr.	VVS nr.	DN	d, ø	arc	X	K	r
370.030.16.1	184039350	200	200 mm	30°	15 cm	2 cm	20 cm
370.055.16.1	184032350	200	200 mm	90°	30 cm	2.5 cm	20 cm
371.015.16.1		250	250 mm	15°	10.3 cm	0 cm	- cm
371.030.16.1	184039370	250	250 mm	30°	16 cm	0 cm	42 cm
371.045.16.1	184036370	250	250 mm	45°	16.5 cm	0 cm	29 cm
371.055.16.1	184032370	250	250 mm	90°	33.5 cm	0 cm	29 cm
372.015.16.1		300	315 mm	15°	10.3 cm	0 cm	- cm
372.030.16.1	184039390	300	315 mm	30°	17 cm	0 cm	47.3 cm
372.045.16.1	184036390	300	315 mm	45°	18 cm	0 cm	32.5 cm
372.055.16.1	184032390	300	315 mm	90°	37 cm	0 cm	32.5 cm