




LOGS WALL

outdoor wall light, LED, 3000K, IP44, square, anthracite, 8W


The indirect LED wall luminaire LOGS WALL is made from aluminium and equipped with a high-performance planar LED. Depending on the version various housing colours are available. The required driver for direct connection to 230V mains supply is included in each package. In addition, the installation can be extended by floor lamps of the series.



TECHNICAL DATA

Item no.	232105
IP Code	IP 65
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	9.5 W
Maximum ambient temperature	40 °C
Level of inrush current	4.7 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.01
Lumen	520 lm
Colour temperature	3000 Kelvin
Color	anthracite
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Width	13 cm
Height	8 cm
Depth	13.2 cm
Net weight	0.925 kg

Light Source

916376	 The logo for AGD, consisting of the letters 'A' and 'G' stacked vertically in a small white box, followed by a green arrow pointing to the right with the letter 'D' inside it.
Gross weight	1.194 kg
BIG WHITE Page	652