

The right power supply for your equipment

Three enclosure formats are available, select the best suited to the space (depending on power). The new devices range from 10 W up to 480 W, for 5 V, 12 V, 24 V, 48 V output voltages.

Ready to fit anywhere

Modular and Optimized Modicon Power Supply devices are among the most compact on the market.

Even easier to install

Up to 6 output terminals (with different marking) make wiring much easier. The full set of product documentation is instantly available thanks to a QR code printed in front of each device. For the modular range, integrated fixing holes allow the devices to be mounted either on DIN (Omega) rail or on panel.

A robust product for peace of mind

Modicon devices can operate up to 70°C. The printed circuit board of the optimized range (book casing) has a conformal coating in order to resist to common dust and chemical pollutants.







(Input 100 ... 240VAC)



24 V	10 W	15 W	30 W	60 W
	ABLM1A24004	ABLM1A24006	ABLM1A24012	ABLM1A24025
12 V		12 W	25 W	50 W
		ABLM1A12010	ABLM1A12021	ABLM1A12042
5 V			18 W	
			ABLM1A05036	

Optimized

(Input 100 ... 240VAC)



	50 W	75 W	90 W	120 W	240 W	480 W
24 V	ABLS1A24021	ABLS1A24031	ABLS1A24038	ABLS1A24050	ABLS1A24100	ABLS1A24200
12 V		ABLS1A12062		ABLS1A12100		
48 V				ABLS1A48025		

Additional information: see product data sheet

Schneider Electric Industries SAS

