


Geberit PE buksegrenør 2 x 30°



Eksempelbillede



Anvendelser

- Til afløb fra bygninger
- Til afvanding af grunde
- Til lodret montering

Egenskaber

- UV-beständig

Tekniske data

Materiale

PE-HD

Varenr.	VVS nr.	DN	d, ø	d1, ø	arc	X1	X2	K1	K2
361.462.16.1	184063250	50 / 50	50 mm	50 mm	60°	5.5 cm	11 cm	3 cm	4 cm
361.459.16.1	184063249	50 / 40	50 mm	40 mm	60°	5.5 cm	11 cm	4 cm	5 cm
363.462.16.1		56 / 50	56 mm	50 mm	60°	6 cm	12 cm	4 cm	5 cm
363.465.16.1		56 / 56	56 mm	56 mm	60°	1.8 cm	5.3 cm	0 cm	0 cm
364.462.16.1	184063262	60 / 50	63 mm	50 mm	60°	6.5 cm	13 cm	5 cm	6 cm
365.465.16.1		70 / 56	75 mm	56 mm	60°	7 cm	14 cm	6 cm	7 cm
365.470.16.1		70 / 60	75 mm	63 mm	60°	7 cm	14 cm	5 cm	6 cm
367.480.16.1	184063309	100 / 90	110 mm	90 mm	60°	9 cm	18 cm	7 cm	7 cm
367.481.16.1	184063310	100 / 100	110 mm	110 mm	60°	9 cm	10.2 cm	5 cm	0 cm