

# PRODUCT DATASHEET

## DOT-it CLASSIC CLASSIC SI

DOT-it | Little helpers



**TECHNICAL DATA**

Electrical data

Nominal wattage	0.23 W
Operating mode	Battery
Nominal voltage	4.5 V

Photometrical data


Color temperature	7000 K
Color rendering index Ra	>80
Light color (designation)	Cool White
Luminous flux	10 lm
Luminous efficacy	43 lm/W

Light technical data

Beam angle	70 ° <sup>1)</sup>
------------	--------------------

<sup>1)</sup> ZMP\_110132

Dimensions & weight



Length	67.0 mm
Width	67.0 mm
Diameter	68.0 mm
Height	22.0 mm
Product weight	83.00 g

Colors & materials

Body material	Acrylonitrile butadiene styrene (ABS)
Product color	Silver
Housing color	Silver

Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...+30 °C
----------------------------------	--------------

### Lifespan

<b>Number of switching cycles</b>	15000
<b>Lifespan</b>	20000 h

### Additional product data

<b>Mounting type</b>	Surface
<b>Mounting location</b>	Wall

### Capabilities

<b>Dimmable</b>	No
<b>LED module replaceable</b>	Not replaceable
<b>Adjustable</b>	No

### Certificates & standards

<b>Protection class</b>	III
<b>Type of protection</b>	IP20
<b>Standards</b>	CE/EAC/REACH/RoHS

---

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075227804	Blister 1	25 mm x 140 mm x 120 mm	98.00 g	0.42 dm <sup>3</sup>
4058075227811	Shipping carton box 6	286 mm x 65 mm x 130 mm	661.00 g	2.42 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.