



APONI 90

outdoor floor stand, LED, 3000K, anthracite, IP65

With the aluminium APONI 90 floor stand, the opalescent PC illumination surface is closed off with an aluminium cap. With protection class IP55, it is suitable for outdoor use. A connection box is optionally available for simplified installation. The luminaire, which comes in two sizes, is connected directly to the 230V mains power supply because of the dimmable LED constant current driver. The APONI series also includes wall lights and can therefore be used universally.

TECHNICAL DATA

| | |
|-----------------------------|------------------------|
| Item no.: | 1000682 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Height | 90.0 cm |
| Diameter | 7.2 cm |
| Net weight | 1.396 kg |
| Gross weight | 2.145 kg |
| IP Code | IP 65 |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ground |
| Wattage | 8.0 W |
| Lumen | 440 lm |
| Colour temperature | 3000 Kelvin |
| Color | anthracite |
| CRI | >80 |
| Binning | 6 |
| LXXBXX data | 70/50 |
| Service life | 30000 h |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| BIG WHITE Page | 549 |



Accessories

| | |
|--------|------------------------------|
| 228730 | CONNECTION BOX , 3-pin, IP68 |
|--------|------------------------------|

Notes
