

Monteringsledninger, PVC-isolerede

Wires, PVC insulated

Standard: HD 21.3

Standard: HD 21.3



Konstruktion:

Construction:

- | | |
|---|--|
| 1 Kobberleder, mangetrådet kl. 5
Copper conductor, stranded, cl. 5 | 2 Isolation, blyfri PVC
Insulation, lead-free PVC |
|---|--|

Anvendelse:

Application:

Monteringsledninger i anlæg omfattet af SB afsnit 6:2001. Indre ledninger i brugsgenstande, belysningsgenstande m.v. i.h.t. konstruktionsforskrifterne. I anlæg omfattet af DS/EN 60439 og DS/EN 60204-1:2006. Må kun installeres af en autoriseret elinstallatør.

Wires used in installations according to regulation SB section 6:2001. For internal wiring in utility products and lighting articles according to construction directions. Covered by DS/EN 60439 and DS/EN 60204-1:2006. Installation to be performed by a licensed electrician only.

Egenskaber:






















Properties:

Mærkespænding AC Rated voltage AC	450/750 V
Prøvespænding DC Test voltage DC	2,5 kV AC
Max. drifttemperatur Max. operating temperature	70 °C
Max. kortslutningstemperatur Max. short-circuit temperature	160 °C
Min. håndteringstemperatur Min. handling temperature	5 °C
Max. lagertemperatur Max. storage temperature	40 °C

Brandprøve Fire test	IEC 60332-1
Min. bøjeradius Min. bending radius	6 x kabel diameter 6 x cable diameter
CE-overensstemmelse CE-conformity	Lavspændingsdirektivet Low Voltage Directive
Certificering Certificat	HAR HAR
RoHS RoHS	Ja Yes







Tekniske data (G):

Technical data (G):

Dimension No. of cores and cross-section	Farve Color	Levering Delivery	Udvendig dimen- sion, nom. Outer diameter, nom.	Udvendig dimen- sion max. Outer diameter max.	Ca. vægt Cable mass approx.	El-nr. Product number	EAN-nr. EAN-nr.
mm ²		m	mm	mm	kg/km		
1G1,5	Grøn/gul Green/yellow	Rg 100	2,9	3,4	19	30 32 306 533	
1G1,5	Grøn/gul Green/yellow	Tb 1800	2,9	3,4	19	30 32 306 135	
1X1,5	Blå Blue	Rg 100	2,9	3,4	19	30 32 306 559	
1X1,5	Blå Blue	Tb 1800	2,9	3,4	19	30 32 306 342	
1X1,5	Brun Brown	Rg 100	2,9	3,4	19	30 32 302 016	
1X1,5	Brun Brown	Tb 1800	2,9	3,4	19	30 32 306 339	
1x1,5	Hvid White	Rg 100	2,9	3,4	19	30 32 215 899	
1X1,5	Mørkegrå Dark grey	Rg 100	2,9	3,4	20	30 32 215 941	
1X1,5	Orange Orange	Rg 100	2,9	3,4	19	30 32 306 562	
1x1,5	Rød Red	Rg 100	2,9	3,4	19	30 32 306 546	
1X1,5	Sort Black	Rg 100	2,9	3,4	19	30 32 302 003	
1X1,5	Sort Black	Tb 1800	2,9	3,4	19	30 32 306 300	
1G2,5	Grøn/gul Green/yellow	Rg 100	3,5	4,1	29	30 32 302 045	
1X2,5	Grøn/gul Green/yellow	Tb 1200	3,5	4,1	29	30 32 307 192	
1x2,5	Blå Blue	Rg 100	3,5	4,1	29	30 32 302 032	
1X2,5	Brun Brown	Rg 100	3,5	4,1	30	30 32 306 520	
1X2,5	Orange Orange	Rg 100	3,5	4,1	29	30 32 221 469	
1X2,5	Rød Red	Rg 100	3,5	4,1	29	30 32 306 517	
1X2,5	Sort Black	Rg 100	3,5	4,1	29	30 32 302 029	
1X2,5	Sort Black	Tb 1200	3,5	4,1	44	30 32 306 313	
1X4	Rød Red	Tb 1000	4,1	4,8	44	30 32 306 261	

Tekniske data (G):

Technical data (G):

Dimension No. of cores and cross-section	Farve Color	Levering Delivery	Udvendig dimen- sion, nom. Outer diameter, nom.	Udvendig dimen- sion max. Outer diameter max.	Ca. vægt Cable mass approx.	El-nr. Product number	EAN-nr. EAN-nr.
mm ²		m	mm	mm	kg/km		
1X4	Sort Black	Rg 100	4,1	4,8	44	30 32 305 026	
1X4	Sort Black	Tb 1000	4,1	4,8	44	30 32 306 274	
1X10	Sort Black	Rg 100	6,0	6,8	110	30 32 235 387	
1X16	Rød Red	Rg 100	7,0	8,1	183	30 32 236 027	
1X25	Sort Black	Rg 100	8,7	10,2	255	30 32 238 245	
1G50	Grøn/gul Green/yellow	Tr 500	11,8	13,9	546	30 32 240 534	

Alle rettigheder forbeholdes. Enhver uautoriseret brug, omfordeling eller gengivelse af dele af eller hele indholdet i enhver form vil udgøre en krænkelse af ophavsretten. Dataene er kun vejledende og skal ikke betragtes som en bindende erklæring eller garanti fra NKT' side vedrørende et produkts egenskaber eller brugbarhed. Datasiden er ikke udtømmende og bør læses i sammenhæng med NKT' andre produktdatablade, uanset om disse er publiceret eller ej. NKT forbeholder sig ret til at ændre datasiden uden forudgående varsel.

All rights reserved. Any unauthorized usage, redistribution or reproduction of part or all of the content in any form will constitute an infringement of copyright. The data are only indicative and should not be considered a binding representation or warranty from NKT concerning a product's properties or usability. The data page is not exhaustive and should be read in conjunction with NKT other product data sheets, whether published or not. NKT reserves the right to change the data page without prior notice.