Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: e3light

Supplier's address: Compliance Department, Moegelgaardsvej 19, 8520 Lystrup, DK

Model identifier: 0103260134

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Nej
Colour-tuneable light source:	Nej	Envelope:	-
High luminance light source:	Nej		
Anti-glare shield:	Nej	Dimmable:	Only with specific dimmers

Product parameters

		i loudet para				
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consum mode (kWh/100 up to the neares	00 h), rounded	5	Energy efficiency class	F		
Useful luminou indicating if it re in a sphere (36 cone (120º) or in (90º)	efers to the flux 50°), in a wide	464 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 624		
On-mode po expressed in W	ower (P _{on}),	5,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	97		
Outer	Height	95	Spectral power	See image		
dimensions	Width	55	distribution in the	in last page		

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	55	range 250 nm to 800 nm, at full-load				
Claim of equival	ent power ^(a)	-	If yes, equivalent power (W)	-			
			Chromaticity coordinates (x and y)	0,466 0,412			
Parameters for LED and OLED light sources:							
R9 colour rende	ring index value	78	Survival factor	0,50			
the lumen main	tenance factor	0,70					
Parameters for	LED and OLED ma	ains light sources:					
displacement fa	ctor (cos φ1)	0,83	Colour consistency in McAdam ellipses	3			
source replaces	an LED light a fluorescent hout integrated icular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (P	st LM)	0,1	Stroboscopic effect metric (SVM)	0,0			

(a)'-' : not applicable;

(b)'-' : not applicable;

