


Geberit PE reduktion centrisk, kort



Eksempelbillede

Anvendelser

- Til afløb fra bygninger
- Til afvanding af grunde

Egenskaber

- Centrisk

- UV-beständig

Tekniske data

Materiale

PE-HD

Varenr.	VWS nr.	DN	d, ø	d1, ø	H	h	K
360.557.16.1	184091239	40 / 30	40 mm	32 mm	8 cm	3 cm	1.5 cm
361.557.16.1	184091248	50 / 30	50 mm	32 mm	8 cm	3 cm	1.5 cm
361.559.16.1	184091249	50 / 40	50 mm	40 mm	8 cm	3 cm	1.5 cm
363.559.16.1	184091254	56 / 40	56 mm	40 mm	8 cm	3 cm	1.5 cm
363.560.16.1	184091255	56 / 50	56 mm	50 mm	8 cm	3 cm	1.5 cm
364.559.16.1	184091261	60 / 40	63 mm	40 mm	8 cm	3 cm	1.5 cm
364.560.16.1	184091262	60 / 50	63 mm	50 mm	8 cm	3 cm	1.5 cm
364.565.16.1	184091266	60 / 56	63 mm	56 mm	8 cm	3 cm	1.5 cm
365.559.16.1	184091272	70 / 40	75 mm	40 mm	8 cm	3 cm	1.5 cm
365.560.16.1	184091273	70 / 50	75 mm	50 mm	8 cm	3 cm	1.5 cm
365.565.16.1	184091278	70 / 56	75 mm	56 mm	8 cm	3 cm	1.5 cm
365.570.16.1	184091274	70 / 60	75 mm	63 mm	8 cm	3 cm	1.5 cm
366.559.16.1	184091286	90 / 40	90 mm	40 mm	8 cm	3 cm	1.5 cm
366.560.16.1	184091287	90 / 50	90 mm	50 mm	8 cm	3 cm	1.5 cm
366.565.16.1	184091292	90 / 56	90 mm	56 mm	8 cm	3 cm	1.5 cm
366.570.16.1	184091288	90 / 60	90 mm	63 mm	8 cm	3 cm	1.5 cm
366.575.16.1	184091289	90 / 70	90 mm	75 mm	8 cm	3 cm	1.5 cm
367.559.16.1	184091305	100 / 40	110 mm	40 mm	8 cm	3 cm	1.5 cm
367.560.16.1	184091306	100 / 50	110 mm	50 mm	8 cm	3 cm	1.5 cm
367.565.16.1	184091300	100 / 56	110 mm	56 mm	8 cm	3 cm	1.5 cm
367.570.16.1	184091307	100 / 60	110 mm	63 mm	8 cm	3 cm	1.5 cm
367.575.16.1	184091308	100 / 70	110 mm	75 mm	8 cm	3 cm	1.5 cm
367.580.16.1	184091309	100 / 90	110 mm	90 mm	8 cm	3 cm	1.5 cm
368.575.16.1	184091317	125 / 70	125 mm	75 mm	8 cm	3 cm	1.5 cm
368.580.16.1	184091318	125 / 90	125 mm	90 mm	8 cm	3 cm	1.5 cm
368.585.16.1	184091319	125 / 100	125 mm	110 mm	8 cm	3 cm	1.5 cm
369.535.16.1	184091327	150 / 100	160 mm	110 mm	4 cm	0.6 cm	0 cm